GOODWE

ESA Series 3-10kW/5-108kWh

Single Phase | All-in-One (HV)

Redefining Home Energy, All-in-One

4S

Silent Smart Secure Simple

Smart: 30%

Bill Savings
AI-driven EMS

Silent: <30dB

Fanless Design for
Quiet Operation

Secure: 6-Layer

Protection
From Cell to System

Simple: 10-min

Installation
Plug. Power. Go

-20°C to 55°C

Operation[1]
Reliable power, any weather

5-108kWh

Mix capacities.
Mix old & new batteries

STS Ready

Built for more scenarios

IP66

protection

<4ms

Backup switching

Up to 63A

Bypass Current
Whole-home backup

200%

PV Oversizing
Charge and power
simultaneously

1: Optional functions or devices are purchased separately

ESA Series / Power Module

GOODWE

Technical Data	GW3K-EHA-G20	GW3.6K-EHA-G20	GW5K-EHA-G20	GW6K-EHA-G20	GW8K-EHA-G20	GW9.999K-EHA-G20
Battery Side						
Battery Type			$LiFePO_4$			
Nominal Battery Voltage (V)			380			
Battery Voltage Range (V)			350 ~ 550			
Start-up Voltage (V)*1			380			
Number of Battery Input			1			
Max. Continuous Charging Current (A)	11.9	14.3	19.8	23.7	31.6	35.6
Max. Continuous Discharging Current (A)	8.7	10.5	14.5	17.4	23.2	29.0
Max. Charging Power (kW)	4.5	5.4	7.5	9.0	12.0	13.5
Max. Discharging Power (kW)	3.3	3.96	5.5	6.6	8.8	11.0
PV Side						
Max. Input Power (kW)	6.0	7.2	10.0	12.0	16.0	20.0
Max. Input Voltage (V)*2			600			
MPPT Operating Voltage Range (V)*3			40 ~ 560			
Start-up Voltage (V)			50			
Nominal Input Voltage (V)			400			
Max. MPPT Current (A)			20			
Max. MPPT Short Circuit Current (A)			26			
Number of MPPTs	2	2	2	2	4	4
Number of Strings per MPPT	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1 / 1 / 1	1 / 1 / 1 / 1
AC Side (On-grid)						
Nominal Power (kW)	3.0	3.6	5.0	6.0	8.0	9.999
Nominal Apparent Power to Grid (kVA)	3.0	3.6	5.0	6.0	8.0	9.999
Max. Apparent Power to Grid (kVA)	3.0	3.6	5.0	6.0	8.0	9.999
Max. Apparent Power from Grid (kVA)*4	6.0	7.2	10.0	12.0	14.5	14.5
Nominal Voltage (V)			220 / 230 / 240, L / N / PE			
Voltage Range (V)			170 ~ 280			
Nominal Frequency (Hz)			50 / 60			
Frequency Range (Hz)			45 ~ 55 / 55 ~ 65			
Max. Current to Grid (A)	13.7 @ 220V 13.1 @ 230V 12.5 @ 240V	16.4 @ 220V 15.7 @ 230V 15.0 @ 240V	22.8 @ 220V 21.8 @ 230V 20.9 @ 240V	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	36.4 @ 220V 34.8 @ 230V 33.4 @ 240V	43.5 @ 220V 43.5 @ 230V 41.7 @ 240V
Max. Current From Grid (A)*4	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	32.8 @ 220V 31.4 @ 230V 30.0 @ 240V	45.5 @ 220V 43.5 @ 230V 41.7 @ 240V	50.0 @ 220V 50.0 @ 230V 50.0 @ 240V	63.0 @ 220V 63.0 @ 230V 60.5 @ 240V	63.0 @ 220V 63.0 @ 230V 60.5 @ 240V
Power Factor			~1 (Adjustable from 0.8 leading to 0.8 lagging)			
THDi			<3%			
Back-up Side						
Nominal Output Apparent Power (kVA)	3.0	3.6	5.0	6.0	8.0	10.0
Max. Output Apparent Power(kVA)	3.0 (6.0, 10s)	3.6 (7.2, 10s)	5.0 (10.0, 10s)	6.0 (12.0, 10s)	8.0 (16.0, 10s)	10.0 (20.0, 10s)
Max. Output Apparent Power (Bypass) (kVA)	6.0	7.2	10.0	12.0	14.5	14.5
Max. Output Current (A)*5	13.7 @ 220V 13.1 @ 230V 12.5 @ 240V	16.4 @ 220V 15.7 @ 230V 15.0 @ 240V	22.8 @ 220V 21.8 @ 230V 20.9 @ 240V	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	36.4 @ 220V 34.8 @ 230V 33.4 @ 240V	43.5 @ 220V 43.5 @ 230V 41.7 @ 240V
Max. Output Current (Bypass) (A)*5	27.3	32.8	45.5	50.0	63.0	63.0
Nominal Output Voltage (V)			220 / 230 / 240, L / N / PE			
Nominal Output Frequency (Hz)			50 / 60			
THDv (@Linear Load)			<3%			
Efficiency						
Max. Efficiency	97.6%	97.6%	97.6%	97.6%	97.5%	97.5%
European Efficiency	96.5%	96.5%	96.8%	97.0%	96.8%	96.8%
Max. Battery to AC Efficiency	98.0%	98.0%	98.0%	98.0%	97.8%	97.8%
Protection						
PV String Current Monitoring			Integrated			
PV Insulation Resistance Detection			Integrated			
Residual Current Monitoring			Integrated			
PV Reverse Polarity Protection			Integrated			
Battery Reverse Polarity Protection			Integrated			
Anti-islanding Protection			Integrated			
AC Overcurrent Protection			Integrated			
AC Short Circuit Protection			Integrated			
AC Overvoltage Protection			Integrated			
DC Surge Protection			Type II			
AC Surge Protection			Type II			
RSD			Optional			
AFCI			Integrated			
Remote Shutdown			Integrated			
General Data						
Operating Temperature Range (°C)			-35 ~ +60 (Derating at +40)			
Relative Humidity			0 ~ 95%			
Max. Operating Altitude (m)			4000 (>2000 derating)			
Cooling Method			Natural convection			
User Interface			LED, WLAN + APP			
Communication with BMS			CAN			
Communication			RS485, WiFI + LAN + Bluetooth ,4G + Bluetooth (Optional)			
Communication Protocols			Modbus-RTU, Modbus-TCP			
Weight (kg)	24	24	24	24	26	26
Dimension (W × H × D mm)			800 × 300 × 270			
Noise Emission	≤30	≤30	≤30	≤30	≤35	≤35
Topology			Non-isolated			
Ingress Protection Rating			IP66			
Mounting Method			Wall / Floor Mounted			
Country of Manufacture			China			

*1: If there's no PV, start-up voltage will be 380V.
*2: When the input voltage is 560V-600V, the inverter will enter standby mode, and the voltage returns to 560V to enter the normal operation state.
*3: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.
*4: GOODWE ESA series has internal bypass 63A passthrough ability to supprt whole home backup solution. If the customer don't want to do any breaker upgrade, the main breaker size in SolarGo (or SEMS+) can be set as previous breaker size.
*5: If the Back-up port is not used, select an appropriate circuit breaker based on the AC Max. Output Current.
*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20261009-AU-V2.1. Information may be subject to change without notice during product improving.

ESA Series / Battery Module*

GOODWE

Technical Data	GW5.1-BAT-D-G20	GW8.3-BAT-D-G20	GW5.1-BAT-D-G21	GW8.3-BAT-D-G21	GW6.0-BAT-D-G20	GW9.0-BAT-D-G20
Battery Type	LFP ($LiFePO_4$)					
Rated Energy (kWh)	5.12	8.32	5.12	8.32	6.0	9.0
Usable Energy (kWh)	5.0*1	8.0*2	5.0*1	8.0*2	5.9*3	8.85*3
Operating Voltage Range (V) (single phase system)	350 ~ 550					
Operating Voltage Range (V) (three phase system)	700 ~ 950					
Max. Input Current (System) (A)	12.0	19.0	12.0	19.0	7.1	10.7
Max. Output Current (System) (A)	13.2	21.0	13.2	21.0	7.9	11.8
Max. Input Power (System) (kW)*4	5.0	8.0	5.0	8.0	3.0	4.5
Max. Output Power (System) (kW)*4	5.0	8.0	5.0	8.0	3.0	4.5
Peak.Output Power (System) (kW)*4	7.5 @10s	12 @10s	7.5 @10s	12 @10s	4.5 @ 10s	6.75 @ 10s
Charging Temperature Range (°C)	-18 ~ +55	-18 ~ +55	+2 ~ +55	+2 ~ +55	-20 ~ +55	-20 ~ +55
Discharging Temperature Range (°C)	-20 ~ +55					
Relative Humidity	4 ~ 100%					
Max. Operating Altitude (m)	4000					
Noise Emission (dB)	≤29	≤29	≤29	≤29	≤27	≤27
Communication	CAN	CAN	CAN	CAN	CAN & 485	CAN & 485
Weight (kg)	57.5 ± 1	79 ± 1	57.5 ± 1	79 ± 1	61 ± 1	77± 1
Ingress Protection	IP66					
Dimensions (W × H × D mm)	800 × 326 × 270					
Function Configuration	Heating (Integrated); Aerosol fire extinguishing (Integrated)		Aerosol fire extinguishing (Integrated)		Heating (Integrated); Aerosol fire extinguishing (Integrated)	
Max. Storage time	12 months (-20°C ~ +35°C) 6 months (+35°C ~ +45°C)					
Scalability*5	12 pcs					
Mounting Method	Floor stacked / Wall-mounted				Floor stacked / Wall-mounted / Grounded	
Cycle Life*6	≥8000	≥8000	≥8000	≥8000	≥10000	≥10000
Country of Manufacture	China					
Standard and Certification – Safety	IEC62619, IEC60730, EN62477, IEC63056, IEC62040, CE, CEC, VDE2510				IEC62619, IEC60730, EN62477, IEC63056, IEC62040, CE, CEC, Regulation 2023 / 1542, VDE2510-50	
Standard and Certification – EMC	CE, RCM					
Standard and Certification – Transportation	UN38.3, ADR					

*1: Test conditions, 98% DOD (cell 2.85~3.6V voltage range), 0.2P charge& discharge at 25+2°C for battery system at the beginning of life. Usable energy is defined by its initial design value. AActual available energy may vary depending on charge/discharge rate, environmental conditions (e.g. temperature), trransport and storage factors.
*2: Test conditions, 96% DOD (cell 2.85~3.6V voltage range), 0.2P charrge & discharge at 25+2°C for battery system at the beginning of life. Usable energy is defined by its initial design value. AActual available energy may vary depending on charge/discharge rate, environmental conditions (e.g. temperature), transport and storage factors.
*3: Test conditions, 98% DOD (cell 2.87~3.61V voltage range), 0.4P charge & discharge at 25±2°C for battery system at the beginning of life. Usable energy is defined by its initial design value. Actual available energy may vary depending on charge/discharge rate, environmental conditions (e.g. temperature), transport and storage factors.
*4: Max. Input Power /Max. Output Power/Peak.Output Power derating will occur related to Temperature and SOC.
*5: For single-column stacked installations, the maximum number of parallel units is 6.
*6: Based on test data under specific laboratory conditions.
*: Based on Lynx D G2 Series technology
*: Please visit GoodWe website for the latest certificates.